



Simply practical

Bend clips for plastic tubes



Simply practical Bend clips for 90° or 45°

- Guidance and protection for tightly curved plastic tubes
- Full flow rate with minimum bending radii
- Simple change of direction possible
- **NEW: now also available assembled**

Bend clip AC 832 90°



Type-d	Mat.-No. non-assembled	Mat.-No. assembled	Size	L	r	g/pc
AC 832-6 90°	988.8325.060	988.8370.060	6	40.0	30	4
AC 832-8 90°	988.8325.080	988.8370.080	8	45.5	35	5
AC 832-10 90°	988.8325.100	988.8370.100	10	54.0	40	14
AC 832-12 90°	988.8325.120	988.8370.120	12	65.0	50	19

Bend clip AC 832 45°



Type-d	Mat.-No. non-assembled	Mat.-No. assembled	Size	L1	L2	r	g/pc
AC 832-8 45°	988.8345.080	988.8375.080	8	42.7	17.7	35	3
AC 832-12 45°	988.8345.120	988.8375.120	12	58.0	24.0	50	12

Packaging unit: Standard: pack of 20 pcs loose half shells or 10 sets bend clips assembled
 BU: pack of 500 pcs loose half shells or 250 sets bend clips assembled
 (ordering example: 988.8325.060.BU)

Material: PA66 GF25, flammability according to UL 94 V0

Operation temperature: -40°C to +130°C

Legende: d = tube outside diameter / r = radius

Types of tubes: suitable for PA, PU, LDPE, PTFE, FEP tubes; not suitable for PVDF tubes

CH: SERTO AG, CH-8500 Frauenfeld, Tel. +41 52 368 11 11, info-ch@serto.com

D: SERTO GmbH, D-34123 Kassel, Tel. +49 561 58004-0, info-de@serto.com

F: SERTO S.A.R.L., F-77164 Ferrières en Brie, Tél. +33 1 64 30 38 38, info-fr@serto.com

I: SERTO Italiana S.r.l., I-20099 Sesto S. Giovanni (Mi), Tel. +39 02 970 641 91, info-it@serto.com

www.serto.com