

Schnellkupplungen Stahl

Innesti rapidi acciaio

Quick couplings steel

Materialien Serie T

- Kuppler und Stecker: Stahl vernickelt
- Dichtungen: NBR (andere auf Anfrage)


Betriebstemperatur

-15°C bis +80°C

Betriebsdruck

20 bar bei +23°C

Kupplungsfunktionen



einseitig absperrend
Kuppler absperrend X-VTC
Stecker nicht absperrend X-PTN

Eigenschaften

- Einhandbedienung
- unter Druck kuppelbar
- kleine Baugrößen

Merkmale

- Einsatz: Druck- und Steuerleitungen, Hydraulik, Chemie
- Medien: Flüssigkeiten, Gase

Materiali serie T

- Innesto femmina e maschio: acciaio nichelato
- Guarnizioni: NBR (altri su richiesta)


Gamma di temperatura

-15°C a +80°C

Pressione di esercizio

20 bar a +23°C

Funzioni



arresto su un lato
innesto femmina con blocco X-VTC
innesto maschio senza blocco X-PTN

Proprietà

- per uso con una sola mano
- accoppiabile sotto pressione
- dimensioni ridotte

Caratteristica

- Applicazione: condotte di misurazione e di comando, settore idraulica e chimica
- Sostanze: fluidi, gas

Materials series T

- Coupler and nipple: nickel plated steel
- Seal: NBR (others on request)


Temperature range

-15°C up to +80°C

Working pressure

20 bar at +23°C

Coupling functions



one-sided shut-off
coupler shut-off X-VTC
nipple no shut-off X-PTN

Properties

- one-handed operation
- can be coupled under pressure
- compact dimensions

Characteristics

- Uses: gauge lines and servo-lines, hydraulic and chemical industry
- Media: fluids, gases

